



PTC 6X30-RP08

TECHNICAL FEATURES

TESTS

Codice

N°	Dati generali sonda	Cod.	Descrizione	Toll.mm
1	SERIES	P1	PTC PROBE STEEL TUBE	
2	ELEMENT	A	PTC KTY 81 - 121 1K 1%	
3	MATERIAL CASE	A	Aisi 304	
4	CASE LENGHT	3	30 mm.	+/- 1.5%
5	Ø CASE	6	6 mm	+/- 1.5%
6	CABLE	P	PVC	
	COLOR		Black	
	DIMENSION		Section 2X0,25 mm² Ø4,6 mm	+/- 1%
7	PROBE LENGHT	8	8 m	+/- 3%
8	CONNECTOR CABLE/CASE	N	None	
9	TERMINAL	P	Pins	
10	FILLING	S	Polyuretan resin	
	EXTRAS			

OPERATING RANGE	(-30+80)°C	MECHANICAL TEST	Cable-case traction kg 2/24 h
TOLERANCE	1%	OHMC CHECK	25°C 1 KOhm
PROTECTION GRADE	IP 67	INSULATION DEGREE	20 Mohm 500 Vcc
RESPONSE TIME	K=10" in liq. V=2m/s	RIGIDITY	2000 Vac



ASCON TECNOLOGIC s.r.l. - 27029 VIGEVANO (PV) Italy - V.le Indipendenza, 56

Tel. 0381 69871 - Fax 0381 698730 - info@ascontecnologic.com - C.F. e P.IVA 02374940183
 Registro Imprese di Pavia n. 02374940183 - R.E.A. n. 268075 - Capitale Sociale Euro 1.000.000,00 i.v.